


T-P-3 SERIES – VOID FILLER (0.50 – 5.00MM SHORE 00 45/65)



DATASHEET



T-P-3 Series (0.50-5.00mm Shore 00 45/65)

FEATURES

- Soft with High Conformability
- 1.5 W/mK Thermal Conductivity
- Low Thermal Impedance
- Naturally Tacky

APPLICATIONS

- Electronic Components: IC, CPU, MOS
- LED, Motherboards, Power Supplies, Heat Sinks, LCD-TV, Notebook PC, PC
- Telecom Devices, Wireless Hub, Automotive and Aerospace applications

PROPERTIES	TEST METHOD	UNIT	T-P-3 SERIES
Material	-	-	Ceramic filled silicon elastomer
Colour	Visual	-	Black
Thickness (±10%) Increments of 0.25mm/0.01inch	-	-	0.5-5.00 0.02-0.20
Thermal Conductivity	ASTM-D5470	W/mK	1.5
Hardness (±10)	ASTM-D2240	Shore 00	45 (≥1.00mm) 65 (<1.00mm)
Flammability Rating	UL94	-	V0
Breakdown Voltage (1.0mm)	ASTM-D149	kV	≥7.5
Specific Gravity	-	g/cm ³	2.7
Working Temperature	-	°C	-40 - 200
Volume Resistance	ASTM-D257	Ohm-cm	10 ¹²
Tensile Strength	ASTM-D412-1998A	Mpa	0.41

THERMAL IMPEDANCE (1.55MM/SHORE 00 60)

Deflection Rate (%)	10	20	30
Thermal Impedance (°C-in ² /W)	1.87	1.68	1.49

NOTES

- Customised shapes are available
- The above performance data is tested in an environment of 70% humidity, temperature 25 °C
- This data is intended for reference purposes only. It is recommended that the material is tested to fully evaluate its performance ensuring it is fit for purpose.

Publish date : 04/05/2020

DK-DALEBA
ORLAND HOUSE
MEAD LANE
HERTFORD
SG13 7AT UK

PHONE: +44(0)1992 510000
EMI@DK-DALEBA.CO.UK
WWW.EMITHERMAL.COM

EMI THERMAL IS A BRAND OF DK-DALEBA