

# T-P-6 SERIES – VOID FILLER (0.50 - 5.00MM SHORE 00 45/65)



## DATASHEET



### FEATURES

- Soft with High Conformability
- 3.0 W/mK Thermal Conductivity
- Low Thermal Impedance
- UL94 V0 Recognised
- Naturally Tacky

### APPLICATIONS

- Electronic Components: IC, CPU, MOS, LED, M/B, P/S, Heat Sinks, LCD-TV's, Notebook PC, PC, Telecommunication Devices
- Wireless Hubs, DDR Modules, DVD Applications, Hand-set Applications etc.

PROPERTIES	TEST METHOD	UNIT	T-P-6 SERIES
Material	-	-	Ceramic filled silicon elastomer
Colour	Visual	-	Blue
Thickness (±10%) Increments of 0.25mm/0.01inch	-	-	0.5-5.00 0.02-0.20
Thermal Conductivity	ASTM-D5470	W/mK	3.0
Hardness (±10)	ASTM-D2240	Shore 00	45 (≥1.00mm) 65 (<1.00mm)
Flammability Rating	UL94	-	V0
Breakdown Voltage (1.0mm)	ASTM-D149	kV	≥7.5
Specific Gravity	-	g/cm <sup>3</sup>	2.89
Working Temperature	-	°C	-40 - 200
Volume Resistance	ASTM-D257	Ohm-cm	10 <sup>12</sup>
Tensile Strength	ASTM-D412-1998A	Mpa	0.23

### THERMAL IMPEDANCE (1.45MM/SHORE 00 65)

Deflection Rate (%)	10	20	30
Thermal Impedance (°C-in <sup>2</sup> /W)	0.83	0.73	0.64

### NOTES

- Customised shapes are available
- The above performance data is tested in an environment of 70% humidity, temperature 25 °C
- This data is intended for reference purposes only. It is recommended that the material is tested to fully evaluate its performance ensuring it is fit for purpose.

Publish date : 04/05/2020

DK-DALEBA  
ORLAND HOUSE  
MEAD LANE  
HERTFORD  
SG13 7AT UK

PHONE: +44(0)1992 510000  
EMI@DK-DALEBA.CO.UK  
WWW.EMITHERMAL.COM

EMI THERMAL IS A BRAND OF DK-DALEBA